



*Anti-Slip Solutions - Slippery surfaces made Safe!*

83 Tuihana Drive Phone: (07) 572-0445  
Papamoa Fax: (07) 572-3127  
Bay of Plenty Email: info@floorsafenz.co.nz  
New Zealand Web: www.floorsafenz.co.nz

## FLOORSAFE STAIR NOSINGS

September 2008

- R-CC** 10um anodised aluminium 25mm x 63mm  
Weight 0.621kg/m. Alloy Temper 6063/T5  
Inserts 42mm self adhesive rubber/cork 2.5mm thick
- R-NA** 10um anodised aluminium. 37mm x 75mm  
Weight 0.770kg/m. Alloy Temper 6063/T5  
Inserts 51mm rubber.
- R-KZ** 10um Anodised Aluminium with bull nose edge 37mm x 80mm  
Weight 0.694kg/m. Alloy Temper 6063/T5
- R-CF** 10um anodised aluminium. 37mm x 71mm  
Weight 0.710kg/m. Alloy Temper 6063/T5  
Inserts 51mm Rubber
- R-NAC** 10um anodised aluminium. 37mm x 75mm  
Weight 0.815kg/m. Alloy Temper 6063/T5  
Inserts 51mm rubber.
- R-MN** 1.6mm Galvanised metal angle coated with a 2-part polyurethane coating.  
The coating is of the highest quality, hard wearing & exceeds the recommendations of HB-197. This nosing also achieves a classification of V according to table 2 AS/NZS 4586:2004

**Floorsafe products are available throughout  
Australia, New Zealand, Malaysia, Brunei, Thailand, Japan & Hong Kong.**